

*Disclaimer: Images are for illustrative purposes.*

## Socket Allen Screw

**Head Style:** Button Head

**Drive Type:** Internal Hex


**Thread Type:** UNC / BSW - Coarse

**Material:** Stainless Steel

**Class Grade:** A2-70 G304

**Corrosion Protection Level:** Excellent

**Standard:** ANSI B18.3



Size	Thread Pitch (TPI)	Thread Type	Product Diameter (D) (mm)		Head Diameter (A) (mm)		Head Height (H) (mm)		Driver Bit Size (AS) (inches)	sku (Part Number)
			Min	Max	Min	Max	Min	Max		
#2-56	56 TPI	Coarse	2.06	2.16	3.92	4.17	0.97	1.17	0	31BSC256
#4-40	40 TPI	Coarse	2.69	2.82	5.11	5.42	1.30	1.50	1/16	31BSC440
#5-40	40 TPI	Coarse	3.03	3.18	5.75	6.05	1.48	1.68	5/64	31BSC540
#6-32	32 TPI	Coarse	3.33	3.48	6.35	6.66	1.61	1.86	5/64	31BSC632
#8-32	32 TPI	Coarse	3.99	4.15	7.57	7.93	1.96	2.21	3/32	31BSC832
#10-24 (3/16")	24 TPI	Coarse	4.60	4.81	8.82	9.17	2.32	2.57	1/8	31BSC1024
1/4"	20 TPI	Coarse	6.15	6.33	10.65	11.10	3.10	3.36	5/32	31BSC14
5/16"	18 TPI	Coarse	7.78	7.93	13.39	13.90	3.87	4.22	3/16	31BSC516
3/8"	16 TPI	Coarse	9.38	9.53	16.16	16.67	4.70	5.06	7/32	31BSC38
1/2"	13 TPI	Coarse	12.53	12.70	21.62	22.23	6.23	6.74	5/16	31BSC12

**Disclaimer:**

Dimensional data and technical information was obtained from publicly available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 17 Mar 2026