

*Disclaimer: Images are for illustrative purposes.*

## Machine Screw

**Head Style:** Countersunk Head

**Drive Type:** Phillips


**Thread Type:** BSW - Coarse

**Material:** Stainless Steel

**Class Grade:** A2-70 G304

**Corrosion Protection Level:** Excellent

**Standard:** ASNI B18.6.3



Size	Thread Pitch (TPI)	Thread Type	Product Diameter (D) (mm)		Head Diameter (A) (mm)		Head Height (H) (mm)		Countersunk Angle		Driver Bit Size (AS)	sku (Part Number)
			Min	Max	Min	Max	Min	Max	Min	Max		
1/8"	40 TPI	Coarse	2.95	3.20	5.11	5.57	1.40	1.71	80-82°	-	PH2	21CSW18
5/32"	32 TPI	Coarse	3.95	4.10	6.46	6.94	1.78	2.04	80-82°	-	PH2	21CSW532
3/16" (#10-24)	24 TPI	Coarse	4.60	4.81	7.80	8.34	2.14	2.54	80-82°	-	PH2	21CSW316
1/4"	20 TPI	Coarse	6.15	6.33	10.47	11.13	2.85	3.36	80-82°	-	PH3	21CSW14
5/16"	18 TPI	Coarse	7.78	7.93	13.16	13.90	3.38	3.81	80-82°	-	PH4	21CSW516

**Disclaimer:**

Dimensional data and technical information was obtained from publicly available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 17 Mar 2026