

Disclaimer: Images are for illustrative purposes.

Machine Screw

Head Style: Countersunk Head

Drive Type: Phillips


Thread Type: Metric - Coarse

Material: Stainless Steel

Class Grade: A4-70 G316

Corrosion Protection Level: Ultimate

Standard: DIN 965 (H)



Size	Thread Pitch (mm)	Thread Type	Product Diameter (D) (mm)		Head Diameter (A) (mm)		Head Height (H) (mm)		Countersunk Angle	Driver Bit Size (AS)	sku (Part Number)
			Min	Max	Min	Max	Min	Max			
M2	0.40mm	Coarse	1.88	1.98	3.50	3.80	0.95	1.25	90°	PH1	21CS2M
M2.5	0.45mm	Coarse	2.38	2.48	4.40	4.70	1.25	1.55	90°	PH1	21CS25M
M3	0.50mm	Coarse	2.87	2.98	5.30	5.60	1.50	1.80	90°	PH1	21CS3M
M4	0.70mm	Coarse	3.83	3.97	7.14	7.50	1.90	2.40	90°	PH2	21CS4M
M5	0.80mm	Coarse	4.82	5.00	8.84	9.20	2.10	2.60	90°	PH2	21CS5M
M6	1.00mm	Coarse	5.82	6.00	10.57	11.00	2.80	3.30	90°	PH3	21CS6M
M8	1.25mm	Coarse	7.78	8.00	14.07	14.50	3.90	4.40	90°	PH4	21CS8M

Disclaimer:

Dimensional data and technical information was obtained from publicly available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 17 Mar 2026