

Disclaimer: Images are for illustrative purposes.

Machine Screw

Head Style: Countersunk Head

Drive Type: Slot


Thread Type: Metric - Coarse

Material: Stainless Steel

Class Grade: A4-70 G316

Corrosion Protection Level: Ultimate

Standard: DIN 963



Size	Thread Pitch (mm)	Thread Type	Product Diameter (D) (mm)		Head Diameter (A) (mm)		Head Height (H) (mm)	Slot Width (SW) (mm)	Countersunk Angle	Driver Bit Size (AS)	sku (Part Number)
			Min	Max	Min	Max	Nom	Nom			
M3	0.50mm	Coarse	2.87	2.98	5.30	5.60	1.65	0.80	90°	SL5	21CSLS3M
M4	0.70mm	Coarse	3.83	3.97	7.14	7.50	2.20	1.00	90°	SL6	21CSLS4M
M5	0.80mm	Coarse	4.82	5.00	8.84	9.20	2.50	1.20	90°	SL8	21CSLS5M
M6	1.00mm	Coarse	5.82	6.00	10.57	11.00	3.00	1.60	90°	SL10	21CSLS6M
M8	1.25mm	Coarse	7.78	8.00	14.07	14.50	4.00	2.00	90°	SL10	21CSLS8M

Disclaimer:

Dimensional data and technical information was obtained from publically available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 17 Mar 2026