

Disclaimer: Images are for illustrative purposes.

Socket Allen Screw

Head Style: Countersunk Head

Drive Type: Internal Hex


Thread Type: Metric - Coarse

Material: Stainless Steel

Class Grade: A2-70 G304

Corrosion Protection Level: Excellent

Standard: DIN 7991 / ISO 10642



Size	Thread Pitch (mm)	Thread Type	Product Diameter (D) (mm)		Head Diameter (A) (mm)		Head Height (H) (mm)	Countersunk Angle	Driver Bit Size (AS) (mm)	sku (Part Number)
			Min	Max	Min	Max	Nom			
M2	0.40mm	Coarse	1.88	1.98	3.85	4.00	1.50	90°	1	31CS2
M2.5	0.45mm	Coarse	2.38	2.48	4.82	5.00	1.86	90°	1	31CS25
M3	0.50mm	Coarse	2.87	2.98	5.54	6.00	1.96	90°	2	31CS3
M4	0.70mm	Coarse	3.83	3.97	7.53	8.00	2.48	90°	2	31CS4
M5	0.80mm	Coarse	4.82	5.00	9.43	10.00	3.44	90°	3	31CS5
M6	1.00mm	Coarse	5.82	6.00	11.34	12.00	3.72	90°	4	31CS6
M8	1.25mm	Coarse	7.78	8.00	15.24	16.00	4.96	90°	5	31CS8
M10	1.50mm	Coarse	9.78	10.00	19.22	20.60	6.20	90°	6	31CS10
M12	1.75mm	Coarse	11.73	12.00	23.12	24.00	7.44	90°	8	31CS12
M16	2.00mm	Coarse	15.73	16.00	29.48	30.00	8.50	90°	10	31CS16

Disclaimer:

Dimensional data and technical information was obtained from publicly available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 17 Mar 2026