

Disclaimer: Images are for illustrative purposes.

Socket Allen Screw

Head Style: Countersunk Head

Drive Type: Internal Hex

Thread Type: Metric - Coarse


Material: Alloy Steel Heat Treated

Class Grade: High Tensile Class 12.9

Finish: Zinc Plated

Corrosion Protection Level: Moderate

Standard: DIN 7991



Size	Thread Pitch (mm)	Thread Type	Product Diameter (D) (mm)		Head Diameter (A) (mm)		Head Height (H) (mm)	Countersunk Angle	Driver Bit Size (AS) (mm)	sku (Part Number)
			Min	Max	Min	Max	Nom			
M3	0.50mm	Coarse	2.87	2.98	5.54	6.00	1.86	90°	2	31C3
M4	0.70mm	Coarse	3.83	3.97	7.53	8.00	2.48	90°	2	31C4
M5	0.80mm	Coarse	4.82	5.00	9.43	10.00	3.10	90°	3	31C5
M6	1.00mm	Coarse	5.82	6.00	11.34	12.00	3.72	90°	4	31C6
M8	1.25mm	Coarse	7.78	8.00	15.24	16.00	4.96	90°	5	31C8
M10	1.50mm	Coarse	9.78	10.00	19.22	20.60	6.20	90°	6	31C10
M12	1.75mm	Coarse	11.73	12.00	23.12	24.00	7.44	90°	8	31CM12

Disclaimer:

Dimensional data and technical information was obtained from publicly available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 17 Mar 2026