

Disclaimer: Images are for illustrative purposes.

Cyclone Roofing Timber Screw

Head Style: Hex Flange Head

Drive Type: Hex

Neo: Multiseal BRA Washer

Screw Point: Type 17 for Timber


Material: Hardened Steel

Class Grade: Class 4 / B8® Cat 5

Finish: Galvanised

Corrosion Protection Level: Excellent

Internal External: External



Size	Thread Pitch (TPI)	Thread Type	Product Diameter (D) (mm)		Head Diameter (A) (mm)		Head Height (H) (mm)	Single Shear (kN)	Axial Tensile (kN)	Torsional (Nm)	Driver Bit Size (AS) (inches)	sku (Part Number)
			Min	Max	Min	Max	Nom					
14g (6.30mm)	10 TPI	Coarse	6.20	6.40	24.50	25.50	6.40	11.600	20.300	20.800	3/8	06CYC4N14

Disclaimer:

Dimensional data and technical information was obtained from publicly available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 17 Mar 2026