

Disclaimer: Images are for illustrative purposes.

Anlock Mega Lock Structural Rivet


Head Style: Countersunk Head

Shell Material: Aluminium

Stem Material: Aluminium

Corrosion Protection Level: Ultimate

Comments: When selecting the right rivet, start with hole size and grip range.



Industry Rivet Code	Rivet Diameter (A) (mm)	Head Diameter (B) (mm)	Shell Length (L) (mm)	Material Grip Range (G) (mm)		Stem Diameter (W) (mm)	Hole Size (mm)		CSK Angle (CA)	Tensile	Shear	sku (Part Number)
		Nom	Nom	Min	Max	Nom	Min	Max	Nom	Nom	Nom	
72 ANAA 6-6	4.80 (3/16)	9.20	12.00	3.20	8.40	3.10	4.90	5.10	120°	1900	2300	72ANAA66
72 ANAA 6-8	4.80 (3/16)	9.20	16.00	7.70	12.70	3.10	4.90	5.10	120°	1900	2300	72ANAA68
72 ANAA 8-8	6.40 (1/4)	11.40	16.00	4.30	12.10	4.10	6.70	6.90	120°	3400	5300	72ANAA88
72 ANAA 8-12	6.40 (1/4)	11.40	23.00	10.50	18.40	4.10	6.70	6.90	120°	3400	5300	72ANAA812

Disclaimer:

Dimensional data and technical information was obtained from publically available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 17 Mar 2026